

TO DEPARTMENT	TO ROOM NAME	ITEM DESCRIPTION	QTY	CAT	SYNOPSIS / DESCRIPTION NOTE	MANUFACTURER	MODEL	ELECTRICAL																							
								VOLT 1	PHASE 1	AMP 1	FREQ 1	WATT 1	CONN 1	PLUG 1	DATA 1	VOLT 2	PHASE 2	AMP 2	FREQ 2	WATT 2	CONN 2	PLUG 2	DATA 2	VOLT 3	PHASE 3	AMP 3	FREQ 3	WATT 3	CONN 3	PLUG 3	DATA 3
Main Kitchen	Receiving	Hand Sink	1	3	Hands free operation, Stainless steel construction, Mixing valve for hot and cold water, High enough above the rim of the sink bowl to enable the washing of arms and hands, Soap dispenser, Single use towel dispenser	EAGLE MASTERS OR EQUAL	HSA-10-FE	120	1	2	60																				
Main Kitchen	Receiving	Eyewash	1	3	Floor or sink mounted emergency eyewash complete with safety mixing valve	SPEAKMAN OR EQUAL	SE-580-ADA																								
Main Kitchen	Receiving	Utility Cart	2	1	Stainless steel construction, type 304, #4 finish, Corner or donut bumpers, Cart washable casters, 180kg capacity	HATCH OR EQUAL	C444-T-HD																								
Main Kitchen	Receiving	Platform Truck	1	1	Stainless steel construction, type 304, #4 finish, Corner or donut bumpers, Cart washable casters, 180kg capacity	HATCH OR EQUAL	HPT2448																								
Main Kitchen	Dry Storage	Shelving, plastic, louvered	8	2	Constructed of steel with removable polypropylene overlays or polyester, thermoplastic/polypropylene construction, Construction to be corrosion resistant and coated with anti-microbial substance, Minimum dimensions to be 530mm wide x 1220mm long, All units to include cart washable casters, two locking, Minimum four tiers of shelves, Shelves to be adjustable	INTERMETRO OR EQUAL METROMAXQ	METROMAXQ																								
Main Kitchen	Dry Storage	Dunnage Rack	4	1	Constructed of polymer with anti-microbial properties or stainless steel, Minimum dimensions to be 560mm wide x 910mm long, 1,500lb capacity minimum.	INTERMETRO OR EQUAL	MHP53K3																								
Main Kitchen	Refrigerated Storage	Walk-In cooler (Dairy/Milk/Juice)	1	3	ULC listed pre-fabricated insulated wall and ceiling panels, 100mm thick with polyurethane insulation, Panels to have a tongue and groove configuration and fastened together with a mechanical cam-lock fastener, Finish to be either white baked enamel, pvc or stainless steel	CURTIS/NORBEC/HUSSMAN/ HILL PHOENIX	CUSTOM	120	1	12											YES	208	3	12			YES	Emergency power to be provided.			
Main Kitchen	Refrigerated Storage	Temperature Alarm	1	3	Hi-low temperature alarm, recessed in wall panels, with dry contacts for remote monitoring, rechargeable battery having operating range of -50C to +50C, Capillary temperature bulbs to be positioned behind evaporator coils (no visible wires)	CURTIS/NORBEC/HUSSMAN/ HILL PHOENIX	CUSTOM																								
Main Kitchen	Refrigerated Storage	Evaporator Coil	1	3	Sized and balanced to match the compressor(s) and must be capable of maintaining internal room temperature (max. +3C for coolers, min. -18C for freezers) while considering humidity levels of surrounding areas, product type and load, heat infiltration and temperature of incoming product Corrosion free assembly, Time initiated air defrost cycles for coolers, Electric or hot gas defrost for freezers. Chilled water cooled compressors.	CURTIS/NORBEC/HUSSMAN/ HILL PHOENIX	CUSTOM																								
Main Kitchen	Refrigerated Storage	Shelving, plastic, louvered	4	2	Constructed of steel with removable polypropylene overlays or polyester, thermoplastic/polypropylene construction, Construction to be corrosion resistant and coated with anti-microbial substance, Minimum dimensions to be 530mm wide x 1220mm long, All units to include cart washable casters, two locking, Minimum four tiers of shelves, Shelves to be adjustable	INTERMETRO OR EQUAL METROMAXQ	METROMAXQ																								
Main Kitchen	Refrigerated Storage	Dunnage Rack	1	1	Constructed of polymer with anti-microbial properties or stainless steel, Minimum dimensions to be 560mm wide x 910mm long, 1,500lb capacity minimum.	INTERMETRO OR EQUAL	MHP53K3																								
Main Kitchen	Refrigerated Storage	Walk-In cooler (Meat)	1	3	ULC listed pre-fabricated insulated wall and ceiling panels, 100mm thick with polyurethane insulation, Panels to have a tongue and groove configuration and fastened together with a mechanical cam-lock fastener, Finish to be either white baked enamel, pvc or stainless steel	CURTIS/NORBEC/HUSSMAN/ HILL PHOENIX	CUSTOM	120	1	12											YES	208	3	12			YES	Emergency power to be provided.			
Main Kitchen	Refrigerated Storage	Temperature Alarm	1	3	Hi-low temperature alarm, recessed in wall panels, with dry contacts for remote monitoring, rechargeable battery having operating range of -50C to +50C, Capillary temperature bulbs to be positioned behind evaporator coils (no visible wires)	CURTIS/NORBEC/HUSSMAN/ HILL PHOENIX	CUSTOM																								
Main Kitchen	Refrigerated Storage	Evaporator Coil	1	3	Sized and balanced to match the compressor(s) and must be capable of maintaining internal room temperature (max. +3C for coolers, min. -18C for freezers) while considering humidity levels of surrounding areas, product type and load, heat infiltration and temperature of incoming product Corrosion free assembly, Time initiated air defrost cycles for coolers, Electric or hot gas defrost for freezers. Chilled water cooled compressors.	CURTIS/NORBEC/HUSSMAN/ HILL PHOENIX	CUSTOM																								
Main Kitchen	Refrigerated Storage	Shelving, plastic, louvered	4	2	Constructed of steel with removable polypropylene overlays or polyester, thermoplastic/polypropylene construction, Construction to be corrosion resistant and coated with anti-microbial substance, Minimum dimensions to be 530mm wide x 1220mm long, All units to include cart washable casters, two locking, Minimum four tiers of shelves, Shelves to be adjustable	INTERMETRO OR EQUAL METROMAXQ	METROMAXQ																								
Main Kitchen	Refrigerated Storage	Dunnage Rack	1	1	Constructed of polymer with anti-microbial properties or stainless steel, Minimum dimensions to be 560mm wide x 910mm long, 1,500lb capacity minimum.	INTERMETRO OR EQUAL	MHP53K3																								

TO DEPARTMENT	TO ROOM NAME	ITEM DESCRIPTION	QTY	CAT	SYNOPSIS / DESCRIPTION NOTE	MANUFACTURER	MODEL	ELECTRICAL																								ELECTRICAL NOTE				
								VOLT 1	PHASE 1	AMP 1	FREQ 1	WATT 1	CONN 1	PLUG 1	DATA 1	VOLT 2	PHASE 2	AMP 2	FREQ 2	WATT 2	CONN 2	PLUG 2	DATA 2	VOLT 3	PHASE 3	AMP 3	FREQ 3	WATT 3	CONN 3	PLUG 3	DATA 3					
Main Kitchen	Refrigerated Storage	Walk-In cooler (Vegetables)	1	3	ULC listed pre-fabricated insulated wall and ceiling panels, 100mm thick with polyurethane insulation, Panels to have a tongue and groove configuration and fastened together with a mechanical cam-lock fastener, Finish to be either white baked enamel, pvc or stainless steel	CURTIS/NORBEC/HUSSMAN/ HILL PHOENIX	CUSTOM	120	1	12								120	1	15						YES	208	3	12					YES	Emergency power to be provided.	
Main Kitchen	Refrigerated Storage	Temperature Alarm	1	3	Hi-low temperature alarm, recessed in wall panels, with dry contacts for remote monitoring, rechargeable battery having operating range of -50C to +50C, Capillary temperature bulbs to be positioned behind evaporator coils (no visible wires)	CURTIS/NORBEC/HUSSMAN/ HILL PHOENIX	CUSTOM																													
Main Kitchen	Refrigerated Storage	Evaporator Coil	1	3	Sized and balanced to match the compressor(s) and must be capable of maintaining internal room temperature (max. +3C for coolers, min. -18C for freezers) while considering humidity levels of surrounding areas, product type and load, heat infiltration and temperature of incoming product Corrosion free assembly, Time initiated air defrost cycles for coolers, Electric or hot gas defrost for freezers. Chilled water cooled compressors.	CURTIS/NORBEC/HUSSMAN/ HILL PHOENIX	CUSTOM																													
Main Kitchen	Refrigerated Storage	Shelving, plastic, louvered	4	2	Constructed of steel with removable polypropylene overlays or polyester, thermoplastic/polypropylene construction, Construction to be corrosion resistant and coated with anti-microbial substance, Minimum dimensions to be 530mm wide x 1220mm long, All units to include cart washable casters, two locking, Minimum four tiers of shelves, Shelves to be adjustable	INTERMETRO OR EQUAL METROMAXQ	METROMAXQ																													
Main Kitchen	Refrigerated Storage	Dunnage Rack	1	1	Constructed of polymer with anti-microbial properties or stainless steel, Minimum dimensions to be 560mm wide x 910mm long, 1,500lb capacity minimum.	INTERMETRO OR EQUAL	MHP53K3																													
Main Kitchen	Refrigerated Storage	Mobile Angle Racks	4	1	Stainless steel construction, type 304, #4 finish, Open all sides with stainless steel base, Base to include marine edge and drain hole, Corner or donut bumpers, Cart washable casters, Slide stops																															
Main Kitchen	Refrigerated Storage	Walk-In Freezer	1	3	ULC listed pre-fabricated insulated wall and ceiling panels, 100mm thick with polyurethane insulation, Panels to have a tongue and groove configuration and fastened together with a mechanical cam-lock fastener, Finish to be either white baked enamel, pvc or stainless steel	CURTIS/NORBEC/HUSSMAN/ HILL PHOENIX	CUSTOM	120	1	12								120	1	15						YES	208	3	12				YES	Emergency power to be provided.		
Main Kitchen	Refrigerated Storage	Temperature Alarm	1	3	Hi-low temperature alarm, recessed in wall panels, with dry contacts for remote monitoring, rechargeable battery having operating range of -50C to +50C, Capillary temperature bulbs to be positioned behind evaporator coils (no visible wires)	CURTIS/NORBEC/HUSSMAN/ HILL PHOENIX	CUSTOM																													
Main Kitchen	Refrigerated Storage	Evaporator Coil	1	3	Sized and balanced to match the compressor(s) and must be capable of maintaining internal room temperature (max. +3C for coolers, min. -18C for freezers) while considering humidity levels of surrounding areas, product type and load, heat infiltration and temperature of incoming product Corrosion free assembly, Time initiated air defrost cycles for coolers, Electric or hot gas defrost for freezers. Chilled water cooled compressors.	CURTIS/NORBEC/HUSSMAN/ HILL PHOENIX	CUSTOM																													
Main Kitchen	Refrigerated Storage	Shelving, plastic, louvered	5	2	Constructed of steel with removable polypropylene overlays or polyester, thermoplastic/polypropylene construction, Construction to be corrosion resistant and coated with anti-microbial substance, Minimum dimensions to be 530mm wide x 1220mm long, All units to include cart washable casters, two locking, Minimum four tiers of shelves, Shelves to be adjustable	INTERMETRO OR EQUAL METROMAXQ	METROMAXQ																													
Main Kitchen	Refrigerated Storage	Dunnage Rack	2	1	Constructed of polymer with anti-microbial properties or stainless steel, Minimum dimensions to be 560mm wide x 910mm long, 1,500lb capacity minimum.	INTERMETRO OR EQUAL	MHP53K3																													
Main Kitchen	Refrigerated Storage	Walk-In Freezer (Dairy)	1	3	ULC listed pre-fabricated insulated wall and ceiling panels, 100mm thick with polyurethane insulation, Panels to have a tongue and groove configuration and fastened together with a mechanical cam-lock fastener, Finish to be either white baked enamel, pvc or stainless steel	CURTIS/NORBEC/HUSSMAN/ HILL PHOENIX	CUSTOM	120	1	12								120	1	15						YES	208	3	12				YES	Emergency power to be provided.		
Main Kitchen	Refrigerated Storage	Temperature Alarm	1	3	Hi-low temperature alarm, recessed in wall panels, with dry contacts for remote monitoring, rechargeable battery having operating range of -50C to +50C, Capillary temperature bulbs to be positioned behind evaporator coils (no visible wires)	CURTIS/NORBEC/HUSSMAN/ HILL PHOENIX	CUSTOM																													
Main Kitchen	Refrigerated Storage	Evaporator Coil	1	3	Sized and balanced to match the compressor(s) and must be capable of maintaining internal room temperature (max. +3C for coolers, min. -18C for freezers) while considering humidity levels of surrounding areas, product type and load, heat infiltration and temperature of incoming product Corrosion free assembly, Time initiated air defrost cycles for coolers, Electric or hot gas defrost for freezers. Chilled water cooled compressors.	CURTIS/NORBEC/HUSSMAN/ HILL PHOENIX	CUSTOM																													

TO DEPARTMENT	TO ROOM NAME	ITEM DESCRIPTION	QTY	CAT	SYNOPSIS / DESCRIPTION NOTE	MANUFACTURER	MODEL	ELECTRICAL																								ELECTRICAL NOTE
								VOLT 1	PHASE 1	AMP 1	FREQ 1	WATT 1	CONN 1	PLUG 1	DATA 1	VOLT 2	PHASE 2	AMP 2	FREQ 2	WATT 2	CONN 2	PLUG 2	DATA 2	VOLT 3	PHASE 3	AMP 3	FREQ 3	WATT 3	CONN 3	PLUG 3	DATA 3	
Main Kitchen	Preparation	Recycle Bin w/Dolly	2	1	Heavy duty refuse container, One piece plastic body construction, Moulded in handles and lift points, Heavy duty cart washable casters	RUBBERMAID OR EQUAL	2640																									
Main Kitchen	Preparation	Organics Bin w/Dolly	2	1	Heavy duty refuse container, One piece plastic body construction, Moulded in handles and lift points, Heavy duty cart washable casters	RUBBERMAID OR EQUAL	2640																									
Main Kitchen	Preparation	Ice Maker	1	2	Self contained air cooled ice machine capable of producing min. of 400lbs of ice in 24hours. Stainless steel exterior, automatic flush, bin, water filter and pre-filter. Cubed ice	HOSHIZAKI OR EQUAL	KM-515-MAH	120	1	13	60																					
Main Kitchen	Preparation	Ice Bin	1	2	Stainless steel ice bin compatible with ice maker, complete with built in drain. 1000lb capacity.	HOSHIZAKI OR EQUAL	B-800-SF																									
Main Kitchen	Production	S.S. Work Table w/Sink	2	2	Stainless steel construction, type 304, #4 finish, Length to suit design x 760mm wide x 910mm high, 1.6mm stainless steel top with 2.0mm stainless steel or galvanized steel sub-top, Hat channel reinforcement to be 3.0mm stainless steel or galvanized steel on centre, Sink to be minimum 506mm x 406mm x 305mm deep complete with hot and cold water faucet with swing spout, Legs to be stainless steel 1.6mm thick, 41mm tubing or square welded to subtop, Stainless steel cross bracing as required, Sound deadening as required, Backsplash to include 19mm radius coved corner, splayed to wall where required, Bullet feet for tables without m/e services, flanged feet secured to floor with s.s. fasteners for tables with m/e services, S.S. drawers	CUSTOM	CUSTOM																									
Main Kitchen	Production	S.S. Work Table w/Utility rack and sink	2	2	Stainless steel construction, type 304, #4 finish, Length to suit design x 760mm wide x 910mm high, 1.6mm stainless steel top with 2.0mm stainless steel or galvanized steel sub-top, Hat channel reinforcement to be 3.0mm stainless steel or galvanized steel on centre, Sinks to be minimum 506mm x 406mm x 305mm deep complete with hot and cold water faucet with swing spout, Legs to be stainless steel 1.6mm thick, 41mm tubing or square welded to subtop, Stainless steel cross bracing as required, Sound deadening as required, Backsplash to include 19mm radius coved corner, splayed to wall where required, Bullet feet for tables without m/e services, flanged feet secured to floor with s.s. fasteners for tables with m/e services, S.S. drawers	CUSTOM	CUSTOM																									
Main Kitchen	Production	Pot Rack	4	2	Constructed or reinforced polymer or stainless steel, Construction to be corrosion resistant and coated with anti-microbial substance, Minimum dimensions to be 610mm wide x 1220mm long, All units to include cart washable casters, two locking, Minimum four tiers of shelves, Shelves to be adjustable	INTERMETRO OR EQUAL	PR48VX2																									
Main Kitchen	Production	Kettle, Twin Steam Jacketed 40 gal with Mixer Arm	1	2	High performance gas-fired kettle, Manual tilting mechanism, 40 gallon capacity, Steam jacketed, 50psi rating minimum, Stainless steel construction, type 304, Spring assisted cover, Double pantry faucet, Tangent draw off valve, Automatic ignition system, Solid state controls for temperature and low water safety. Vertical mixer arm attachment.	CLEVELAND OR EQUAL	HA-MKGL-40-T	208	3	15	60																					
Main Kitchen	Production	Kettle, steam jacketed 25 gallon, tilting	1	2	High performance gas-fired kettle, Manual tilting mechanism, 25 gallon capacity, Steam jacketed, 50psi rating minimum, Stainless steel construction, type 304, Spring assisted cover, Double pantry faucet, Tangent draw off valve, Automatic ignition system, Solid state controls for temperature and low water safety	CLEVELAND OR EQUAL	KGL-25-T	120	1	15	60																					
Main Kitchen	Production	Tilt Skillet 40 Gallon	1	2	Heavy duty gas skillet, Tilting mechanism (manual or power), 150litre capacity, High efficiency heating system, Stainless steel construction, type 304, Tangent draw off valve, Adjustable electronic thermostat, Spring assisted cover, Double pantry faucet, Electronic spark ignition	CLEVELAND OR EQUAL	SGL-40T	120	3	10	60																					
Main Kitchen	Production	Kettle, 12 Gallon With Stand	1	2	High performance electric kettle, Manual tilting mechanism, 12 gallon capacity, Steam jacketed, 50psi rating minimum, Stainless steel construction, type 304, Solid state controls for temperature and low water safety	CLEVELAND OR EQUAL	TKET-12-T	208	3	34.1	60																		Emergency power to be provided.			
Main Kitchen	Production	Immersion blender	1	1	Commercial grade, hand held immersion blender, 450 mm shaft, continuous on feature, complete with cord and plug	WARING OR EQUAL	WSB 60	120	1	5	60																					
Main Kitchen	Production	Full Size Oven-Steamer, Combination, Gas	2	2	Full size combination convection/steam oven, Sized to accept full size baking sheets and gastronorm 1/1 pans (20), Programmable cooking modes, Core temperature probe, High performance steam generator, Haccp data memory and output capabilities, Water conditioning kit, Safety door lock, Chicken roasting racks.	CLEVELAND OR EQUAL	OGS 20.20	208	3	25	60																		Emergency power to be provided.			
Main Kitchen	Production	Double Deck Convection Oven	1	2	Double deck electric convection oven with 11KW heating elements, 2 speed 1/2 hp motor and interior lights. Complete with standard solid state controls.	SOUTHBEND OR EQUAL	ES-20	208-240	3	35	60																					
Main Kitchen	Production	Double Compartment Steamer	1	1	2 compartment stacked on each other, 12 pan high efficiency boilerless convection steamer.	CLEVELAND OR EQUAL	24-CGA-10	208-240	3	45	60																					
Main Kitchen	Production	Deep Fryer, Gas	2	2	High production, gas fired stand alone fryer with tube burner, stainless steel cabinet, millivolt thermostat, high temperature safety limit switch. 50 lb capacity.	PITCO OR EQUAL	SG-14R																									

TO DEPARTMENT	TO ROOM NAME	ITEM DESCRIPTION	QTY	CAT	SYNOPSIS / DESCRIPTION NOTE	MANUFACTURER	MODEL	ELECTRICAL																								ELECTRICAL NOTE								
								VOLT 1	PHASE 1	AMP 1	FREQ 1	WATT 1	CONN 1	PLUG 1	DATA 1	VOLT 2	PHASE 2	AMP 2	FREQ 2	WATT 2	CONN 2	PLUG 2	DATA 2	VOLT 3	PHASE 3	AMP 3	FREQ 3	WATT 3	CONN 3	PLUG 3	DATA 3									
Main Kilchen	Production	Heavy Duty Range, griddle	2	2	Heavy duty gas griddle range w/oven below (standard or convection oven), Minimum 860mm wide, Separate controls for each burner, Flame failure protection and electronic spark ignition, Stainless steel exterior construction, type 304 with either porcelain or stainless steel interior.	SOUTHBEND OR EQUAL	P-36A-GGG	120	1	5	60																													
Main Kilchen	Production	Heavy Duty Range	1	2	Heavy duty gas range w/oven below (standard or convection oven), Minimum 860mm wide, Separate controls for each burner, Flame failure protection and electronic spark ignition, Stainless steel exterior construction, type 304 with either porcelain or stainless steel interior. Unit can be	SOUTHBEND OR EQUAL	P-36A-BBB	120	1	5	60																													
Main Kilchen	Production	S.S. service wall	1	2	38mm steel angle frame construction with removable s.s. panels. 1.6mm s.s. service chase at both ends complete with 1.25mm s.s. removable panels. Removable access panels with recessed handles. Provide all necessary service openings for connection of services to equipment. Provide s.s. grommets to conceal all openings for services. Recessed switches and receptacles as required for equipment. Hinged, louvered door with magnetic closers at top and bottom at each end.	CUSTOM	CUSTOM																																	
Main Kilchen	Production	Trench Drain	3	3	Stainless steel construction, type 304, #4 finish. Length and width to suit design x 150mm deep. All radius corners, 1.6mm stainless steel pan Honeycomb or other patterned grating.	CUSTOM	CUSTOM																																	
Main Kilchen	Production	Exhaust Hood w/Fire Protection System	1	3	Box type or island type high efficiency ventilator with integral make-up air plenum. Sized to suit equipment below (ensure minimum 200mm overhang on all sides), ULC listed and CGA approved, Meets NFPA-96 standards (most recent version), Stainless steel liquid tight construction, Easy access to all components, Fire dampers, Fire dampers activated by thermostatic or mechanical detection, Mechanical gas valve. Interconnection to building automation and/or fire systems	HALTON OR SPRING AIR	VAR	120	1	15	60																													
Main Kilchen	Production	Control Panel w/Fire Protection System	1	3	ULC listed wet chemical fire suppression system to provide full coverage of ventilator, plenums, ducts and appliances. Remote pull stations as required. Variable speed type ventilators shall be considered. Ventilator types which reduce exhaust volumes shall be considered, Exhaust air shall filter through an ecology unit, Fire protection systems	HALTON OR SPRING AIR	VAR	120	1	15	60																													
Main Kilchen	Production	Hand Sink	1	3	Hands free operation, Stainless steel construction, Mixing valve for hot and cold water, High enough above the rim of the sink bowl to enable the washing of arms and hands, Soap dispenser, Single use towel dispenser	EAGLE MASTERS OR EQUAL	HSA-10-FE																																	
Main Kilchen	Production	Eyewash	1	3	FLOOR OR SINK MOUNTED EMERGENCY EYEWASH COMPLETE WITH HAND CONTROL AND SAFETY MIXING VALVE	SPEAKMAN OR EQUAL																																		
Main Kilchen	Bulk Meal Assembly	S.S. Mobile Work Table	2	1	Stainless steel construction, type 304, #4 finish. Maximum 1800mm long x 610mm - 910mm wide x 910mm high, 1.6mm stainless steel top with 2.0mm stainless steel or galvanized steel sub-top, Hat channel reinforcement to be 3.0mm stainless steel or galvanized steel on centre, Boxed or marine edges, Legs to be stainless steel 1.6mm thick, 41mm tubing or square welded to subtop, Stainless steel cross bracing as required, Sound deadening as required, Cart washable casters, two locking	CUSTOM	CUSTOM																																	
Main Kilchen	Bulk Meal Assembly	Roll in hot holding cabinet, double door with racks	1	1	Mobile holding oven. Two individually controlled oven compartments. Stainless steel interior and exterior. Pass through doors. Digital controls. Door venting. Solid state electronic control. Window doors.	ALTO-SHAAM	1000-UP	120	1	16	60																													
Main Kilchen	Bulk Meal Assembly	Roll in refrigerator, double door with racks	1	2	Two full door section roll-in refrigerator, Minimum 1.5 cubic metre capacity, Stainless steel interior and exterior, type 304, +3C operating temperature, Casters, two locking, PVC coated interior shelves, No R22 refrigerant, Coved interior corners	TRUE	STA2RRI-2S	120	1	12	60																													
Main Kilchen	Bulk Meal Assembly	Waste Bin w/dolly	2	1	Heavy duty refuse container, One piece plastic body construction, Moulded in handles and lift points, Heavy duty cart washable casters	RUBBERMAID OR EQUAL	2640																																	
Main Kilchen	Bulk Meal Assembly	Insulated Transport Cart	12	1	All stainless steel construction insulated meal cart, pass thru door design. Complete with top rail. This cart to be compatible with meal delivery heating system, tray and plate systems. Size and capacity to be confirmed with users.	HATCH OR EQUAL	VAR																																	
Main Kilchen	Bulk Meal Assembly	Secure Insulated Transport Cart	4	1	All stainless steel construction insulated meal cart, complete with correctional security package, complete with top rail. This cart to be compatible with meal delivery heating system, tray and plate systems. Size and capacity to be confirmed with users.	HATCH OR EQUAL	VAR																																	
Main Kilchen	Bulk Meal Assembly	Hand Sink	1	3	Hands free operation, Stainless steel construction, Mixing valve for hot and cold water, High enough above the rim of the sink bowl to enable the washing of arms and hands, Soap dispenser, Single use towel dispenser	EAGLE MASTERS OR EQUAL	HSA-10-FE																																	
Main Kilchen	Janitor Closet	Hand Sink	1	3	Hands free operation, Stainless steel construction, Mixing valve for hot and cold water, High enough above the rim of the sink bowl to enable the washing of arms and hands, Soap dispenser, Single use towel dispenser	EAGLE MASTERS OR EQUAL	HSA-10-FE																																	

TO DEPARTMENT	TO ROOM NAME	ITEM DESCRIPTION	QTY	CAT	SYNOPSIS / DESCRIPTION NOTE	MANUFACTURER	MODEL	ELECTRICAL																										
								VOLT 1	PHASE 1	AMP 1	FREQ 1	WATT 1	CONN 1	PLUG 1	DATA 1	VOLT 2	PHASE 2	AMP 2	FREQ 2	WATT 2	CONN 2	PLUG 2	DATA 2	VOLT 3	PHASE 3	AMP 3	FREQ 3	WATT 3	CONN 3	PLUG 3	DATA 3	ELECTRICAL NOTE		
Main Kitchen	Warewashing	Soiled pot wash table with 3 sinks and Disposer	1	2	Stainless steel construction. Complete with sound deadening materials between sheets of stainless steel and support membranes. Type 304, #4 finish. Length to suit design x 760mm wide x 910mm high. Sinks to be minimum 610mm x 508mm x 350mm deep for wash and rinse sinks and 760mm x 508mm x 350mm deep for soak sinks complete with hot and cold water faucet with swing spout and one pre-rinse faucet, 1.6mm stainless steel top with 2.0mm stainless steel or galvanized steel sub-top, bHat channel reinforcement to be 3.0mm stainless steel or galvanized steel on centre, Tops to include rolled edges, Slope landing areas to sink. Legs to be stainless steel 1.6mm thick, 41mm tubing or square welded to subtop, Stainless steel cross bracing as required, Sound deadening as required, Backsplash to be minimum 300mm high and include 19mm radius coved corner, splayed to wall where required, Bullet feet for tables without m/e services, flanged feet secured to floor with s.s. fasteners for tables with m/e services, S.S. wall panels, 760mm high fixed to wall above backsplash at all sides	CUSTOM + WASTE EXPRESS	CUSTOM + WX300	208	3	12	60																							
Main Kitchen	Warewashing	Pot washer, ELECTRIC	1	2	Self-contained, automatic cart washer complete with stainless steel tank, chamber, frame and feet. Heavy duty 5 hp motor, door interlock switch and low water protection. Chamber capable of accommodating 16 full sized sheet pans and capable of processing 19 racks per hour.	HOBART OR EQUAL	UW 50	208	3	94	60																							
Main Kitchen	Warewashing	Condensate Hood	1	3	Box type, Sized to suit machine (ensure minimum 200mm overhang on sides and 450mm in front of unit), Stainless steel liquid tight construction, Condensate baffles, Drain outlet	HALTON OR SPRING AIR	VAR	120	1	10	60																							
Main Kitchen	Warewashing	S.S. clean dish table	1	1	Stainless steel construction. Complete with sound deadening materials between sheets of stainless steel and support membranes. Type 304, #4 finish, Dimensions to suit design and dishwasher selected and to provide access all around for cleaning, 2.0mm stainless steel top and integral drain. Provide all necessary interconnections to limit switch and dishwasher.	CUSTOM	CUSTOM																											
Main Kitchen	Warewashing	Organic Waste Digester Connected to Disposers	1	2	self-contained, continual feed, organic food waste elimination system to convert food waste into water using a combination of mechanical processing, heat, oxygen and all-natural additives to accelerate the natural aerobic decomposition process. Organic waste to be reduced to a gray water effluent that can be safely disposed of into existing municipal waste water systems.	ENVIROPURE	EPW	208-230	3	40	60																							
Main Kitchen	Warewashing	Pot Rack	4	1	Constructed or reinforced polymer or stainless steel. Construction to be corrosion resistant and coated with ant-microbial substance, Minimum dimensions to be 610mm wide x 1220mm long. All units to include cart washable casters, two locking. Minimum four tiers of shelves, Shelves to be adjustable. Provide pot/pan inserts.	INTERMETRO OR EQUAL	PR48VX2																											
Main Kitchen	Warewashing	Hand Sink	1	3	Hands free operation, Stainless steel construction, Mixing valve for hot and cold water, High enough above the rim of the sink bowl to enable the washing of arms and hands, Soap dispenser, Single use towel dispenser	EAGLE MASTERS OR EQUAL	HSA-10-FE	120	1	5	60																							
Main Kitchen	Warewashing	Eyewash	1	3	Floor or sink mounted emergency eyewash complete with safety mixing valve	SPEAKMAN OR EQUAL	SE-580-ADA																											
Main Kitchen	Warewashing	Waste Bin w/Dolly	4	1	Heavy duty refuse container, One piece plastic body construction, Moulded in handles and lift points, Heavy duty cart washable casters	RUBBERMAID OR EQUAL	2640																											
Main Kitchen	Cart Wash	Hose Reel with Gun complete with control box	1	2	Hot and cold water mixing valve (hose bib connection), Capable of automatic chemical injection, Spray gun with adjustable nozzles	FISCHER OR EQUAL	29629																											
Main Kitchen	Cart Wash	Trench Drain	1	3	Stainless steel construction, type 304, #4 finish, Length and width to suit design x 150mm deep, All radius corners, 1.6mm stainless steel pan Honeycomb or other patterned grating, removable in sections, Provide strainer at all drains	CUSTOM	CUSTOM																											
Main Kitchen	Cart Wash	Stainless steel wall cladding	1	3	2.0mm stainless steel wall panels applied to the complete interior (walls and ceiling) of cart wash area, Stainless steel trim where panels join together to form a water tight join	CUSTOM	CUSTOM																											

ITEM DESCRIPTION	PLUMBING																																					
	W 1		PRESSURE 1				FLUID 2	ID 2		OD 2		CODE 2	CONN 2	FLOW 2				PRESSURE 2				FLUID 3	ID 3		OD 3		CODE 3	CONN 3	FLOW 3				PRESSURE 3					
	PEAK		LOW		HIGH			INCH	MM	INCH	MM			AVERAGE		PEAK		LOW		HIGH			INCH	MM	INCH	MM			AVERAGE		PEAK		LOW		HIGH			
	GAL/MIN	LPS	PSI	KPA	PSI	KPA	GAL/MIN					LPS	GAL/MIN	LPS	PSI	KPA	PSI	KPA	GAL/MIN	LPS	GAL/MIN	LPS					PSI	KPA	PSI	KPA	GAL/MIN	LPS	GAL/MIN	LPS	PSI	KPA	PSI	KPA
Hand Sink							HW		13											ID		38																
Eyewash							HW		19																													
Cart, Utility																																						
Coffee brewer																																						
Hot Water Dispenser																																						
Ice/Water Dispenser							ID		1@19 1@13																													
Milk Dispenser																																						
Juice Dispenser																																						
Roll in hot holding cabinet, single door with racks																																						
Roll in refrigerator, double door with racks																																						
Self Serve Air Screen Wall Refrig. Showcase																																						
Display Case, Non-Refrigerated, Countertop																																						
Drop-In, Soup Well																																						
4 Well Hot/Cold Convertible Food Unit																																						
Plate lowerator, built in																																						
Toaster, Conveyor																																						
Griddle, Double-Sided, Electric																																						
Microwave																																						
Sandwich/Salad Prep Unit																																						
Trash Can W/Dolly																																						
Recycle Bin w/Dolly																																						
Organics Bin w/Dolly																																						
Sneeze guard																																						
Millwork Counter, Front																																						
Millwork Counter, Rear																																						
Millwork Condiment Counter																																						
Microwave oven																																						
Millwork Trash Station																																						
Millwork Cash Station																																						
Trash Can W/Dolly																																						
Recycle Bin w/Dolly																																						
Organics Bin w/Dolly																																						
Tray Return Carts																																						
Point of Sale System																																						
Digital Menu Board																																						

ITEM DESCRIPTION	PLUMBING																									
	FLUID 3		ID 3		OD 3		CODE 3	CONN 3	FLOW 3		PRESSURE 3		FLUID 4		ID 4		CODE 4	CONN 4	FLOW 4		PRESSURE 4					
	INCH	MM	INCH	MM			AVERAGE	PEAK	LOW	HIGH	INCH	MM			AVERAGE	PEAK	LOW	HIGH	MBTUH	LPS	GAL/ LPS	PSI	KPA	PSI	KPA	
							GAL/ LPS	GAL/ LPS	PSI	KPA					PSI	KPA										
Millwork Counter																										
Refrigerated Display Case																										
Ambient Display Case																										
Coffee Maker, Automatic																										
Hot Water Dispenser																										
Hot Powdered Drink Dispenser																										
Undercounter Refrigerator																										
Reach-in Refrigerator																										
Reach-in Freezer																										
Back counter with sink																										
Over cupboards																										
Hands Free Hand Sink	ID		38																							
Waste Bin w/dolly																										
Undercounter Warewasher, hi temp																										
3 compartment sink	D		3@38																							
Point of Sale System																										
Millwork Condiment Counter																										
Digital Menu Board																										

TO ROOM NAME	ITEM DESCRIPTION	QTY	CAT	SYNOPSIS / DESCRIPTION NOTE	MANUFACTURER	MODEL										
							VOLT 1	PHASE 1	AMP 1	FREQ 1	WATT 1	CONN 1	PLUG 1	DATA 1		
Servery's	Millwork Back Counter w/ Sink	1	3	Custom fabricated millwork counter, complete with stainless steel sink, dimensions, accessories and convenience receptacles to suit design.	CUSTOM	CUSTOM										
Servery's	Millwork Overcupboards	1	3	Custom fabricated millwork overcupboards, dimensions and accessories to suit design.	CUSTOM	CUSTOM										
Servery's	Hands Free Hand Sink	1	3	Hands free operation, Stainless steel construction, Mixing valve for hot and cold water, High enough above the rim of the sink bowl to enable the washing of arms and hands, Soap dispenser, Single use towel dispenser, Waste bin.	EAGLE MASTERS OR EQUAL	HSA-10-FE	120	1	2	60						
Servery's	Millwork Front Counter	1	3	Custom fabricated millwork counter, dimensions, accessories and convenience receptacles to suit design.	CUSTOM	CUSTOM										
Servery's	Drop-In, Soup Wells	1	1	Deep drawn stainless steel round warming pan complete with tubular element, dial thermostat, built in drain, and recessed controls. Capable of wet or dry operation	WELLS OR EQUAL	SS-10-ULTD	208/240	1	16	60						
Servery's	4 Well hot/cold food table	1	1	Convertible hot/cold drop in pan complete with electric immersion heating system and self-contained air cooled condensing unit. ULC listed and NSF-7 compliant with auto fill feature and built in drain. Complete with adapter bars.	WELLS OR EQUAL	HRCF-7400	208/240	1	35	60						
Servery's	Plate lowerator, built in	1	1	Stainless steel construction, field, adjustable self levelling plate dispenser, capacity to be confirmed with users. To be included as part of meal delivery system. Confirm plate size with Owner.	HATCH OR EQUAL	TO SUIT DESIGN										
Servery's	Pass Through Refrigerated Display	1	1	Vertical upright pass-through refrigerated air curtain merchandiser complete with adjustable shelving and self contained refrigeration.	STRUCTURAL CONCEPTS OR EQUAL	B4732P	208	1	12	60						
Servery's	Toaster, Conveyor	1	1	Stainless steel construction, type 304, High volume toast and bagel toaster (minimum 75mm opening), Multiple heating elements, Insulated construction, Toast collector pan, toast feed ramp and removable crumb tray	HATCO OR EQUAL	TQ-1800	208	1	22	60						
Servery's	Coffee Maker, Airpot, Automatic	1	2	Hard wired automatic pourover coffee maker complete with airpots. Twin brew head system capable of brewing 56 litres per hour. Complete with hot water faucet	BUNN OR EQUAL	CWTF TWIN	240	1	28	60						
Servery's	Dispenser, Hot Water	1	2	Hot water boiler with faucet, Capacity 2 gallons, complete with water filter	BUNN OR EQUAL	HW-2	240	1	28	60						
Servery's	Reach-In Refrigerator	1	1	One full door section refrigerator, Minimum 0.74 cubic metre capacity, Stainless steel interior and exterior, type 304, +3C operating temperature, Casters, two locking, PVC coated interior shelves, No R22 refrigerant, Coved interior corners	TRUE OR EQUAL	T-23	120	1	8	60						
Servery's	Microwave Oven	1	2	Commercial grade, 10 touch pad control panel shall be programmable, 5 power level, 1800 watt output, 1.2 cubic foot capacity.	AMANA OR EQUAL	MFS-18TS	208/240	1	20	60						
Servery's	Sneeze Guards	2	1	Fully adjustable modular glass panel sneeze guards capable of 360° adjustment. UL and NSF listed.	BSI OR EQUAL	Z-Guard										
Servery's	Utility Cart	1	2	Stainless steel construction, type 304, #4 finish, Corner or donut bumpers, Cart washable casters, 180kg capacity	HATCH OR EQUAL	C444-T-HD										
Servery's	Washer, Undercounter, High Temp	1	1	Undercounter washer capable of washing 30 racks per hour, hot water wash with built in booster heater capable of 70° rise.	HOBART OR EQUAL	Lxi	208/240	1	38	60						
Servery's	Waste Bin W/Dolly	1	1	Heavy duty refuse container, One piece plastic body construction, Moulded in handles and lift points, Heavy duty cart washable casters	RUBBERMAID OR EQUAL	2640										
Servery's	Cart, Utility	1	1	Stainless steel construction, type 304, #4 finish, Corner or donut bumpers, Cart washable casters, 180kg capacity	HATCH OR EQUAL	C444-T-HD										
Servery's	Tray Return Cart	2	1	Stainless steel construction, type 304, #4 finish, Open all sides with stainless steel base, Base to include marine edge and drain hole, Corner or donut bumpers, Cart washable casters, Slide stops. Confirm tray or pan sizes with owner.	HATCH OR EQUAL	TO SUIT DESIGN										

ITEM DESCRIPTION	ELECTRICAL															FLUID 1	ID 1		OD 1		CODE 1	CONN 1	FLOW 1		PRESSURE 1				
	VOLT 2	PHASE 2	AMP 2	FREQ 2	WATT 2	CONN 2	PLUG 2	DATA 2	VOLT 3	PHASE 3	AMP 3	FREQ 3	WATT 3	CONN 3	PLUG 3		DATA 3	INCH	MM	INCH			MM	AVERAGE	PEAK	LOW	HIGH		
																								GAL/LPS	GAL/LPS	PSI	KPA	PSI	KPA
Millwork Back Counter w/ Sink																													
Millwork Overcupboards																													
Hands Free Hand Sink																	CW												
Millwork Front Counter																													
Drop-In, Soup Wells																	ID												
4 Well hot/cold food table																	ID												
Plate lowerator, built in																													
Pass Through Refrigerated Display																													
Toaster, Conveyor																													
Coffee Maker, Airpot, Automatic																	CW												
Dispenser, Hot Water																	CW												
Reach-In Refrigerator																													
Microwave Oven																													
Sneeze Guards																													
Utility Cart																													
Warewasher, Undercounter, High Temp																	HW												
Waste Bin W/Dolly																													
Cart, Utility																													
Tray Return Cart																													

TO ROOM NAME	ITEM DESCRIPTION	QTY	CAT	SYNOPSIS / DESCRIPTION NOTE	MANUFACTURER	MODEL								
							VOLT 1	PHASE 1	AMP 1	FREQ 1	WATT 1	CONN 1	PLUG 1	DATA 1
Nutrition Centre	Millwork Counter w/ Sink	1	3	Custom fabricated millwork counter, complete with stainless steel sink, dimensions, accessories and convenience receptacles to suit design.	CUSTOM	CUSTOM								
Nutrition Centre	Millwork Overcupboards	1	3	Custom fabricated millwork overcupboards, dimensions and accessories to suit design.	CUSTOM	CUSTOM								
Nutrition Centre	Domestic refrigerator/freezer	1	1	Domestic type, stand-up style refrigerator with top freezer section	DOMESTIC	DOMESTIC								
Nutrition Centre	Domestic kettle	1	1	Plug in type dometic kettle.	DOMESTIC	DOMESTIC								
Nutrition Centre	Ice/Water Dispenser	1	2	Compact, touch free ice/water dispenser capable of producing up to 520 pounds of nugget ice per day with a 26 pound storage capacity.	SCOTSMAN OR EQUAL	MDT5N25	120	1	20	60				
Nutrition Centre	Domestic toaster	1	1	Plug in type dometic toaster	DOMESTIC	DOMESTIC								
Nutrition Centre	Domestic coffee brewer	1	1	Plug in type dometic coffee brewer	DOMESTIC	DOMESTIC								
Nutrition Centre	Domestic microwave	1	1	Plug in type dometic microwave	DOMESTIC	DOMESTIC								
Nutrition Centre	Waste Bin W/Dolly	1	1	Heavy duty refuse container, One piece plastic body construction, Moulded in handles and lift points, Heavy duty cart washable casters	RUBBERMAID OR EQUAL	2640								

ITEM DESCRIPTION	FLUID 5	ID 5		CODE 5	CONN 5	FLOW 5		PRESSURE 5				HVAC									
		INCH	MM			AVERAGE	PEAK	LOW		HIGH		BTU/ HR	MAX BTU/ HR	DUCT WIDTH		DUCT HEIGHT		CFM	IN (WG)	LPS	KPA
						GAL/ LPS	GAL/ LPS	PSI	KPA	PSI	KPA			INCH	MM	INCH	MM				
Millwork Counter w/ Sink																					
Millwork Overcupboards																					
Domestic refrigerator/freezer																					
Domestic kettle																					
Ice/Water Dispenser																					
Domestic toaster																					
Domestic coffee brewer																					
Domestic microwave																					
Waste Bin W/Dolly																					

TO ROOM NAME	ITEM DESCRIPTION	QTY	CAT	SYNOPSIS / DESCRIPTION NOTE	MANUFACTURER	MODEL										
							VOLT 1	PHASE 1	AMP 1	FREQ 1	WATT 1	CONN 1	PLUG 1	DATA 1		
Acute Care Servery	Millwork Back Counter w/ Sink	2	3	Custom fabricated millwork counter, complete with stainless steel sink, dimensions, accessories and convenience receptacles to suit design.	CUSTOM	CUSTOM										
Acute Care Servery	Millwork Overcupboards	1	3	Custom fabricated millwork overcupboards, dimensions and accessories to suit design.	CUSTOM	CUSTOM										
Acute Care Servery	Hands Free Hand Sink	2	3	Hands free operation, Stainless steel construction, Mixing valve for hot and cold water, High enough above the rim of the sink bowl to enable the washing of arms and hands, Soap dispenser, Single use towel dispenser, Waste bin.	EAGLE MASTERS OR EQUAL	HSA-10-FE	120	1	2	60						
Acute Care Servery	Millwork Front Counter	2	3	Custom fabricated millwork counter, dimensions, accessories and convenience receptacles to suit design.	CUSTOM	CUSTOM										
Acute Care Servery	Drop-In, Soup Wells	2	1	Deep drawn stainless steel round warming pan complete with tubular element, dial thermostat, built in drain, and recessed controls. Capable of wet or dry operation	WELLS OR EQUAL	SS-10-ULTD	208/24	1	16	60						
Acute Care Servery	4 Well hot/cold food table	2	1	Convertible hot/cold drop in pan complete with electric immersion heating system and self-contained air cooled condensing unit. ULC listed and NSF-7 compliant with auto fill feature and built in drain. Complete with adapter bars.	WELLS OR EQUAL	HRCP-7400	208/24	1	35	60						
Acute Care Servery	Plate lowerator, built in	2	1	Stainless steel construction, field, adjustable self levelling plate dispenser, capacity to be confirmed with users. To be included as part of meal delivery system. Confirm plate size with Owner.	HATCH OR EQUAL	TO SUIT DESIGN										
Acute Care Servery	Pass Through Refrigerated Display	2	1	Vertical upright pass-through refrigerated air curtain merchandiser complete with adjustable shelving and self contained refrigeration.	STRUCTURAL CONCEPTS OR EQUAL	B4732P	208	1	12	60						
Acute Care Servery	Toaster, Conveyor	2	1	Stainless steel construction, type 304, High volume toast and bagel toaster (minimum 75mm opening), Multiple heating elements, Insulated construction, Toast collector pan, toast feed ramp and removable crumb tray	HATCO OR EQUAL	TQ-1800	208	1	22	60						
Acute Care Servery	Coffee Maker, Airpot, Automatic	2	2	Hard wired automatic pourover coffee maker complete with airpots. Twin brew head system capable of brewing 56 litres per hour. Complete with hot water faucet	BUNN OR EQUAL	CWTF TWIN	240	1	28	60						
Acute Care Servery	Dispenser, Hot Water	1	2	Hot water boiler with faucet, Capacity 2 gallons, complete with water filter	BUNN OR EQUAL	HW-2	240	1	28	60						
Acute Care Servery	Reach-In Refrigerator	1	1	Two full door sections refrigerator, Minimum 0.74 cubic metre capacity, Stainless steel interior and exterior, type 304, +3C operating temperature, Casters, two locking, PVC coated interior shelves, No R22 refrigerant, Coved interior corners	TRUE OR EQUAL	T-49	120	1	11	60						
Acute Care Servery	Ice/Water Dispenser	1	2	Compact, touch free ice/water dispenser capable of producing up to 520 pounds of nugget ice per day with a 26 pound storage capacity.	SCOTSMAN OR EQUAL	MDT5N25	120	1	20	60						
Acute Care Servery	Microwave Oven	1	1	Commercial grade, 10 touch pad control panel shall be programmable, 5 power level, 1800 watt output, 1.2 cubic foot capacity.	AMANA OR EQUAL	MFS-18TS	208/24	1	20	60						
Acute Care Servery	Sneeze Guards	2	2	Fully adjustable modular glass panel sneeze guards capable of 360° adjustment. UL and NSF listed.	BSI OR EQUAL	Z-Guard										
Acute Care Servery	Utility Cart	4	1	Stainless steel construction, type 304, #4 finish, Corner or donut bumpers, Cart washable casters, 180kg capacity	HATCH OR EQUAL	C444-T-HD										
Acute Care Servery	Waste Bin W/Dolly	1	1	Heavy duty refuse container, One piece plastic body construction, Moulded in handles and lift points, Heavy duty cart washable casters	RUBBERMAID OR EQUAL	2640										
Acute Care Servery	Cart, Utility	1	1	Stainless steel construction, type 304, #4 finish, Corner or donut bumpers, Cart washable casters, 180kg capacity	HATCH OR EQUAL	C444-T-HD										
Acute Care Servery	Tray Return Cart	6	1	Stainless steel construction, type 304, #4 finish, Open all sides with stainless steel base, Base to include marine edge and drain hole, Corner or donut bumpers, Cart washable casters, Slide stops. Confirm tray or pan sizes with owner.	HATCH OR EQUAL	TO SUIT DESIGN										

ITEM DESCRIPTION	ELECTRICAL															FLUID 1	ID 1		OD 1		CODE 1	CONN 1	FLOW 1		PRESSURE 1				
	VOLT 2	PHASE 2	AMP 2	FREQ 2	WATT 2	CONN 2	PLUG 2	DATA 2	VOLT 3	PHASE 3	AMP 3	FREQ 3	WATT 3	CONN 3	PLUG 3		DATA 3	INCH	MM	INCH			MM	AVERAGE	PEAK	LOW	HIGH		
																								GAL/LPS	GAL/LPS	PSI	KPA	PSI	KPA
Millwork Back Counter w/ Sink																													
Millwork Overcupboards																													
Hands Free Hand Sink																	CW		13										
Millwork Front Counter																													
Drop-In, Soup Wells																	ID		13										
4 Well hot/cold food table																	ID		13										
Plate lowerator, built in																													
Pass Through Refrigerated Display																													
Toaster, Conveyor																													
Coffee Maker, Airpot, Automatic																	CW		9										
Dispenser, Hot Water																	CW		9										
Reach-In Refrigerator																													
Ice/Water Dispenser																	CW		2@9										
Microwave Oven																													
Sneeze Guards																													
Utility Cart																													
Waste Bin W/Dolly																													
Cart, Utility																													
Tray Return Cart																													

ITEM DESCRIPTION	FLUID 4		ID 4	CODE 4	CONN 4	FLOW 4				PRESSURE 4				FLUID 5	ID 5	CODE 5	CONN 5	FLOW 5				PRESSURE 5				HVAC							
	AVERAGE	PEAK				LOW	HIGH	LOW	HIGH	LOW	HIGH	AVERAGE	PEAK					LOW	HIGH	AVERAGE	PEAK	LOW	HIGH	BTU/HR	MAX BTU/HR	DUCT WIDTH	DUCT HEIGHT	CFM	IN (WG)	LPS	KPA		
	MBTUH	LPS	GAL/LPS	PSI	KPA	PSI	KPA	PSI	KPA	INCH	MM	GAL/LPS	GAL/LPS	PSI	KPA	PSI	KPA	HR	HR	INCH	MM	INCH	MM	LPS	KPA								
	INCH	MM																															
Millwork Back Counter w/ Sink																																	
Millwork Overcupboards																																	
Hands Free Hand Sink																																	
Millwork Front Counter																																	
Drop-In, Soup Wells																																	
4 Well hot/cold food table																																	
Plate lowerator, built in																																	
Pass Through Refrigerated Display																																	
Toaster, Conveyor																																	
Coffee Maker, Airpot, Automatic																																	
Dispenser, Hot Water																																	
Reach-In Refrigerator																																	
Ice/Water Dispenser																																	
Microwave Oven																																	
Sneeze Guards																																	
Utility Cart																																	
Waste Bin W/Dolly																																	
Cart, Utility																																	
Tray Return Cart																																	

ITEM DESCRIPTION	PLUMBING NOTE	HVAC										
		BTU/HR	MAX BTU/HR	DUCT WIDTH INCH	DUCT WIDTH MM	DUCT HEIGHT INCH	DUCT HEIGHT MM	CFM	IN (WG)	LPS	KPA	HVAC NOTE
Hand Sink												
Eyewash												
Utility Cart												
S.S. Work Table w/sink												
Roll in hot holding cabinet, double door with rack												
Roll in refrigerator, double door with racks												
Reach-in Refrigerator												
Reach-in Freezer												
Soiled dish Table w/pre-rinse and 3 comp. sink												
Door Type Warewasher												
Condensate Hood							1000					
Clean Dish Table												
Tray lowerators												
Dish rack lowerators												
Dish dispensers												
Pot Rack												
Shelving, Plastic Louvered												
Waste Bin w/dolly												
Recycle Bin w/Dolly												
Organics Bin w/Dolly												
Hand Sink, Janitor												
Mop Sink												

ITEM DESCRIPTION	PLUMBING NOTE	HVAC										
		BTU/HR	MAX BTU/HR	DUCT WIDTH		DUCT HEIGHT		CFM	IN (WG)	LPS	KPA	HVAC NOTE
				INCH	MM	INCH	MM					
Shelving, plastic, louvered, Janitor												